

Features
Merkmale

Side-/bottom-hung
Dreh, Kipp

Double-vent
Stulp

Db-thr. Locking
Gegenläufig

Easy-access
Barrierefrei

Shaped windows
Schräglügel

Composite vents
Verbundflügel

Accessories
Zubehör



Kammergetriebe 23

Einschwenkbar, für Schüco Steckgriffe und Befestigungsrosetten
Befestigungsabstand: 23 mm

Cavity-fitted gearbox 23

Slot-in, for Schüco push-in window handles and fixing rosettes
Fixing distance: 23 mm

Farbe Colour	LS	RS	
silber	277 033	277 034	1
Silver	277 035	277 036	10



Anbohrschutz für RC 1 N erforderlich.
Drill protection required for RC 1 N.
RC-Case Kammergetriebe für RC 2 und RC 3 erforderlich.
RC security plate for cavity-fitted gearbox, required for RC 2 and RC 3.



Symmetrisches Kammergetriebe 23

Einschwenkbar, RS/LS verwendbar, ermöglicht geringere Mindestflügelgrößen und geringere Lagerhaltung, für Schüco Steckgriffe und Befestigungsrosetten.
Befestigungsabstand: 23 mm

Symmetrical cavity-fitted gearbox 23

Slot-in, can be used RS/LS, enables lower minimum vent sizes and reduced stock quantities, for Schüco push-in window handles and fixing rosettes.
Fixing distance: 23 mm

Farbe Colour	LS/RS	
silber	277 180	1
Silver	277 181	10



Anbohrschutz für RC 1 N erforderlich.
Drill protection required for RC 1 N.



RC-Case für symmetrisches Kammergetriebe für RC 2 und RC 3 erforderlich.
RC security plate for symmetrical cavity-fitted gearbox required for RC 2 and RC 3.